


DEMS 390-390A-390B



Çalışma Limitleri

Basınç: 0~1MPa
Hız: ≤20m/s
Sıcaklık: -20°C~+180°C

Operating Limits

Pressure: 0~1MPa
Speed: ≤20m/s
Temperature: -20°C~+180°C

- Döner Yüzey (SiC/TC)
- Sabit Eleman (Carbon/SiC/TC)
- Elastomer (EPDM/ITON/PTFE)
- Yay & Diğer Parçalar (SUS304/SUS316)
- Rotary Ring (SiC/TC)
- Stationary Ring (Carbon/SiC/TC)
- Secondary Seal (EPDM/ITON/PTFE)
- Spring & Other Parts (SUS304/SUS316)

Seal size d(mm)	d ₃	d ₄	d ₆	d ₇	d ₅	d ₈	l (±0.5)	l ₁ (±0.5)	l ₄	c
		min								
18	32	34	27	33	23	3	52.0	45.0	5	2.0
20	34	36	29	35	25	3	52.0	45.0	5	2.0
22	36	38	31	37	27	3	53.0	46.0	5	2.0
24	38	40	33	39	29	3	56.0	49.0	5	2.0
25	39	41	34	40	30	3	56.0	49.0	5	2.0
28	42	44	37	43	33	3	56.5	49.5	5	2.0
30	44	46	39	45	35	3	57.0	50.0	5	2.0
32	46	48	42	48	38	3	58.5	51.5	5	2.0
33	47	49	42	48	38	3	58.5	51.5	5	2.0
35	49	51	44	50	40	3	58.5	51.5	5	2.0
38	54	58	49	56	44	4	62.0	55.0	6	2.0
40	56	60	51	58	46	4	62.0	55.0	6	2.0
43	59	63	54	61	49	4	65.0	58.0	6	2.0
45	61	65	56	63	51	4	65.0	58.0	6	2.0
48	64	68	59	66	54	4	66.0	59.0	6	2.0
50	66	70	62	70	57	4	67.0	60.0	6	2.5
53	69	73	65	73	60	4	71.5	64.5	6	2.5
55	71	75	67	75	62	4	73.5	66.5	6	2.5
58	78	83	70	78	65	4	76.5	69.5	6	2.5
60	80	85	72	80	67	4	76.5	69.5	6	2.5
63	83	88	75	83	70	4	78.5	71.5	6	2.5
65	85	90	77	85	72	4	81.5	74.5	6	2.5
68	88	93	81	90	75	4	82.5	75.5	7	2.5
70	90	95	83	92	77	4	86.5	79.5	7	2.5
75	99	104	88	97	82	4	87.0	80.0	7	2.5
80	104	109	95	105	88	4	90.5	83.5	7	3.0
85	109	114	100	110	93	4	90.5	83.5	7	3.0
90	114	119	105	115	98	4	92.5	85.5	7	3.0
95	119	124	110	120	103	4	93.5	86.5	7	3.0
100	124	129	115	125	108	4	93.5	86.5	7	3.0